

PG-Keys: Keys for Property Graphs

Linked Data Benchmark Council
Property Graph Schema Working Group

LDBC TUC 18 June 2022

PG-Keys team: from industry, academia, ISO, LDBC, PGSWG

Renzo Angles Universidad de Talca, IMFD Chile

Angela Bonifati Lyon 1 Univ., Liris CNRS & INRIA

Stefania Dumbrava ENSIIE & Inst. Polytech. de Paris

George Fletcher Eindhoven Univ. of Technology

Keith W. Hare JCC Consulting Inc., Neo4j

Jan Hidders Birkbeck, Univ. of London

Victor E. Lee TigerGraph

Bei Li Google

Leonid Libkin U. of Edinburgh, ENS-Paris/PSL

Wim Martens University of Bayreuth

Filip Murlak University of Warsaw

Josh Perryman Interos Inc.

Ognjen Savković Free Univ. of Bozen-Bolzano

Michael Schmidt Amazon Web Services

Juan Sequeda data.world

Sławek Staworko U. Lille, INRIA LINKS, CRISAL CNRS

Dominik Tomaszuk Inst. of Comp. Sci., U. of Białystok

Why PG-Keys?

Why Keys for Property Graphs?

Keys are ... key in data management for identifying, referencing and constraining objects.

For example, `Person` nodes

- are **uniquely identified** by their login ID
- can be **referenced** using one of their email addresses (and it is **mandatory** that each person has at least one email), of which **at most one** can be the preferred email.
- have zero or more aliases which are **exclusive** (i.e., no two people can share an alias)

and discussion `Forum` nodes are **identified** by the forum's name and the person who moderates the forum

- `(:Person)<-[:hasModerator]-(:Forum)`

Why Keys for Property Graphs?

Keys are vital for managing both **identity** and **integrity** in the graph

- Example: for an integrated knowledge graph, modeling key constraints in underlying data sources and in maintaining data quality and consistency in the graph itself.

Why Now?

Because property graphs technologies are being standardized now in ISO

- LDDB and its PGSWG is a community of researchers, practitioners, and database vendors working towards consensus recommendations informing this process

and, furthermore, system vendors are moving ahead in diverse ways ...

Current Graph DB Support for Keys is Limited

Landscape is *diverse*:

- Some systems offer property-based primary keys for nodes
- Some systems support uniqueness
- Some systems support mandatoriness

Yet we need to support all of these, and more, to satisfy current practical needs.



There is already a *significant drift* between database vendors

We need to *get on the same page*

We need to *bring the best of academic work to the needs of industry*

Guided tour of PG-Keys

Our proposal: PG-Keys



Design requirements

1. Flexible choice of **key scope** and **descriptor of key values**.
2. Keys for nodes, edges, and properties.
3. Identify, reference, and constrain objects.
4. Easy to validate.

Flexible choice of scope and key values

Declaratively specify the **scope** of the key and its **values** in your favourite PG query language (a parameter of PG-Keys). Here we use Cypher-like syntax.


For instance

```
FOR p WITHIN (p:Person) IDENTIFIER p.login;
```

says that “each **person** is identified by **their login**”, and

```
FOR f WITHIN (f:Forum) <-[:joined]-(:Person)
IDENTIFIER f.name, p WITHIN (f) <-[:moderates]-(:Person);
```

says that “each **forum with a member** is identified by **its name and moderator**”.



Keys for nodes, edges, and properties

The scope query selects a set of **nodes**, **edges**, or property values.

For instance,


```
FOR p WITHIN (p:Person) IDENTIFIER p.login;
```

says that “each **Person node** is identified by the value of property **login**”, and

```
FOR e WITHIN (:Person)-[e:joined]->(:Forum)
```

```
IDENTIFIER p,f WITHIN (p:Person)-[e:joined]->(f:Forum);
```

says that “each **joined edge** is identified by its endpoints (i.e., no other **joined edge** has the same endpoints, so one cannot join the same forum twice)”.



Identify, reference, and constrain objects

Identification is provided by IDENTIFIER:

```
FOR f WITHIN (f:Forum)<-[:joined]-(:Person)
IDENTIFIER f.name, p WITHIN (f)<-[:moderates]-(p:Person)
```


IDENTIFIER means:

EXCLUSIVE - no objects in the scope share a key value;

MANDATORY - each object in the scope has at least one key value;

SINGLETON - each object in the scope has at most one key value.

In SQL, EXCLUSIVE is UNIQUE, MANDATORY is NOT NULL, and SINGLETON is always ensured by 1NF. In property graphs, all three are needed.



Identify, reference, and constrain objects

Referencing is provided by EXCLUSIVE MANDATORY:


```
FOR p WITHIN (p:Person)
EXCLUSIVE MANDATORY e WITHIN (p)-[:has]->(e:Email);
```

That is, “emails are not shared and each person has an email”.

Constraining can be done in many ways. For example,

```
FOR p WITHIN (p:Person)
EXCLUSIVE p.alias;

FOR p WITHIN (p:Person)
EXCLUSIVE SINGLETON e WITHIN (p)-[:preferred]->(e:Email);
```



Easy to validate

To check that a PG-Key holds, we can run queries to find violations.

For instance,


```
FOR p WITHIN (p:Person)
EXCLUSIVE MANDATORY e WITHIN (p)-[:has]->(e:Email);
```

holds if both queries below return nothing:

```
MATCH (p1:Person)-[:has]->(e:Email)<-[:has]-(p2:Person)
WHERE p1 <> p2 RETURN p1, p2;
```

```
MATCH (p:Person)
WHERE NOT EXISTS (p1:Person)-[:has]->(e:Email);
```

Incremental validation or batching will require additional mechanisms.



Extending PG-Keys

Null Values

If the data can have null values, then we need to know what


```
FOR p WITHIN (p:Person) WHERE p.age > 30
...;
```

means if `p.age` can be NULL.

Our approach:

Design PG-Keys such that one can validate a key K by executing a query Q_K that finds violations of K

We thought everything through again to see to which extent this goal can be reached; essentially, enforce “`p.age > 30 AND p.age IS NOT NULL`”



Regular Path Queries

If posts in forums can reply to other posts, then


```
FOR x WITHIN (x:Post)
```

```
IDENTIFIER p WITHIN
```

```
p = (x)-[:replyTo*]->()->[:OP]->(f:Forum);
```

means that

“Each post is identified by its reply-to path in the forum where it was posted”



Complex Values

Our data model already allows complex values such as

tuples sets lists JSON structures


In order to use these in PG-Keys, we leverage the query language:

```
FOR p WITHIN (p:Person)
```

```
EXCLUSIVE MANDATORY
```


```
p.phone[@.category='official'].number;
```

- “Each person has an official telephone number” and
- “No two persons have the same official telephone number”



Looking Ahead

Looking ahead



- PG-Keys is a call to action also to industry and academia
 - Guide the design and engineering of commercial and non-commercial graph systems and solutions
 - Open problems for research include:
 - Validation and maintenance complexity for specific query languages
 - Implication and inference problems
 - Static analysis for optimization purposes
 - Richer PG constraint languages
- And PGSWG is just getting started!
 - Design of PG schema and constraint languages
 - Extensions to the PG model driven by practical applications, e.g., meta-properties.