


The Train Benchmark: Cross-Technology Performance Evaluation of Continuous Model Queries

Gábor Szárnyas

**MTA-BME Lendület Research Group on Cyber-Physical Systems
Fault Tolerant Systems Research Group**

McGill University, Department of Electrical and Computer Engineering



McGill

LDBC benchmarks

- Graphalytics
- Semantics Publishing Benchmark
- Social Network Benchmark
 - Interactive
 - Business Intelligence

LDBC benchmarks

- Graphalytics
- Semantics Publishing Benchmark
- Social Network Benchmark
 - Interactive
 - Business Intelligence

Small updates

Local patterns

LDBC benchmarks

- Graphalytics
- Semantics Publishing Benchmark
- Social Network Benchmark

- Interactive

Small updates

Local patterns

- Business Intelligence

Large updates

Global patterns

LDBC benchmarks

- Graphalytics
- Semantics Publishing Benchmark
- Social Network Benchmark
 - Interactive
 - Business Intelligence


Small updates

Global patterns


Model-Driven Engineering

Modeling


Model-Driven Engineering




Model-Driven Engineering




Model-Driven Engineering




Model-Driven Engineering




Model-Driven Engineering



Model-Driven Engineering



Model-Driven Engineering



Model Sizes

- **Models = graphs** with 100M–1B elements

- Car industry



- Avionics

- Software analysis

- Cyber-physical systems

application	model size
software models	10^8
sensor data	10^9
geo-spatial models	10^{12}

Source: Markus Scheidgen, *Automated and Transparent Model Fragmentation for Persisting Large Models*, 2012

Model Sizes

- **Models = graphs** with 100M–1B elements

- Car industry



- Avionics

- Software analysis


- Cyber-physical systems

Validation may take hours


application	model size
software models	10^8
sensor data	10^9
geo-spatial models	10^{12}

Source: Markus Scheidgen, *Automated and Transparent Model Fragmentation for Persisting Large Models*, 2012


Railway example




Railway example




Railway example




Railway example




Railway example




Railway example




Railway example




Railway example




Railway example




Railway example




Railway example




Railway example




Railway example




Railway instance model




Railway instance model




Railway instance model




Railway instance model




Railway instance model




Railway instance model




Railway instance model




Railway instance model




Railway instance model




Railway instance model




Railway instance model



Railway instance model



Railway instance model



Benchmark criteria

Benchmark criteria

Early 1990s:

Benchmark criteria

Early 1990s:

before the „browser wars”

Benchmark criteria

Early 1990s:

Benchmark criteria

Early 1990s:

„benchmark wars”

Benchmark criteria

Early 1990s:

„benchmark wars”

Jim Gray, *Benchmark Handbook*, 1993

Criteria for domain-specific benchmarks:

Benchmark criteria

Early 1990s:


„benchmark wars”

Jim Gray, *Benchmark Handbook*, 1993

Criteria for domain-specific benchmarks:

- Relevant
- Scalable
- Portable
- Simple


Benchmark phases



Query →

Change set size →
{fixed, proportional}

Benchmark phases




Query →

Change set size →
{fixed, proportional}

1. Load

Benchmark phases




Query →

Change set size →
{fixed, proportional}




Benchmark phases




Query →

Change set size →
{fixed, proportional}



Benchmark phases




Query →

Change set size →
{fixed, proportional}




Benchmark phases




Query →

Change set size →
{fixed, proportional}




Benchmark phases




Query →

Change set size →
{fixed, proportional}




Benchmark phases




Query →


Change set size →
{fixed, proportional}




Benchmark phases



Benchmark phases




Benchmark phases




Railway model

- Synthetic model
- Customizable model generator




EMF metamodel



EMF metamodel


Containment hierarchy



EMF metamodel

Containment hierarchy

No opposite references




EMF metamodel

Containment hierarchy

No opposite references


Inheritance



EMF metamodel

Containment hierarchy

No opposite references



Enumerations

Inheritance


Instance model generation

- Randomly generated with increasing sizes
 - 1, 2, 4, ...
- Violations are inserted during generation
- Multiple formats:
 - EMF
 - property graph
 - RDF
 - SQL


EMF model




Property graph



RDF with metamodel



RDF with inferred tuples



Validation and transformation

- Well-formedness constraints

Validation and transformation

- Well-formedness constraints
- Queries are looking for **error patterns**

Validation and transformation

- Well-formedness constraints
- Queries are looking for **error patterns**
 - Lots of filtering, joins, etc.

Validation and transformation

- Well-formedness constraints
- Queries are looking for **error patterns**
 - Lots of filtering, joins, etc.
- Transformations


Validation and transformation

- Well-formedness constraints
- Queries are looking for **error patterns**
 - Lots of filtering, joins, etc.
- Transformations
 - Fault injections
 - Quick fix-like repair operations


Queries



(a)




(b)




(c)

Queries



(e)


Queries




route1 ≠ route2

(f)

Transformation



Transformation



Threats to validity

Threats to validity

- **Operating system:** caching, scheduled jobs

Threats to validity

- **Operating system:** caching, scheduled jobs
- **Cloud noise** from the environment


Threats to validity

- **Operating system:** caching, scheduled jobs
- **Cloud noise** from the environment
- **Parallel processes & multithreaded execution**


Threats to validity

- **Operating system:** caching, scheduled jobs
- **Cloud noise** from the environment
- **Parallel processes & multithreaded execution**
- **Managed runtime environments**
 - Java Virtual Machine
 - .NET CLR

The effect of warmup




The effect of warmup




Two Java-based query engines


The effect of warmup



The effect of warmup




The effect of warmup



First execution time


The effect of warmup



First execution time

Median execution time of 5 executions

The effect of warmup



Benchmark environment

- Quad-core Xeon CPU
- SSD
- 16 GB RAM
- Ubuntu 14.04 with Oracle Java 8





Benchmark environment



- Quad-core Xeon CPU
- SSD
- 16 GB RAM
- Ubuntu 14.04 with Oracle Java 8



Support for
educational users







Inject scenario, execution time













Batch scenario, memory consumption



Lessons learnt

Lessons learnt

- Contact tool authors for assistance

Lessons learnt

- Contact tool authors for assistance
- Very hard to tell the **actual** memory consumption
 - Manual calls to the garbage collector – not enough
 - Profiler – still not enough
 - Setting a hard limit is the best approach

Lessons learnt

- Contact tool authors for assistance
- Very hard to tell the **actual** memory consumption
 - Manual calls to the garbage collector – not enough
 - Profiler – still not enough
 - Setting a hard limit is the best approach
- Difficult to get **relevant results**

Lessons learnt

- Contact tool authors for assistance
- Very hard to tell the **actual** memory consumption
 - Manual calls to the garbage collector – not enough
 - Profiler – still not enough
 - Setting a hard limit is the best approach
- Difficult to get **relevant results**
 - Lots of factors can add noise to the results

Lessons learnt


- Contact tool authors for assistance
- Very hard to tell the **actual** memory consumption
 - Manual calls to the garbage collector – not enough
 - Profiler – still not enough
 - Setting a hard limit is the best approach
- Difficult to get **relevant results**
 - Lots of factors can add noise to the results
 - Nothing works on the first try

Lessons learnt

- Contact tool authors for assistance
- Very hard to tell the **actual** memory consumption
 - Manual calls to the garbage collector – not enough
 - Profiler – still not enough
 - Setting a hard limit is the best approach
- Difficult to get **relevant results**
 - Lots of factors can add noise to the results
 - Nothing works on the first try
- Visualization helps **a lot**
 - Automate with R/Python script


Train Benchmark summary

- Scalable model generator
 - 4 representation formats
- Realistic workload
 - 6 validation queries
 - 12 transformations
 - Implemented for 12+ tools
- Visualization and reporting



Train Benchmark summary

- Scalable model generator
 - 4 representation formats
- Realistic workload
 - 6 validation queries
 - 12 transformations
 - Implemented for 12+ tools
- Visualization and reporting



Gábor Szárnyas, Benedek Izsó, István Ráth, Dániel Varró:

The Train Benchmark: cross-technology performance evaluation of continuous model queries, SOSYM 2017,

<http://link.springer.com/article/10.1007/s10270-016-0571-8>